



Product Specifications

Grand Slam - HOPSCOTCH



<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>		
Surface Composition	100% PVC			
Finished Width	54" min.	ASTM D 751-06		
Weight at 54 inches	37.5 oz/yd	ASTM D 751-06		
Thickness	1.25 mm ±10%	ASTM D 751-06		
Total Weight	25.0 oz./yd ² ±10%	ASTM D 751-06		
Backing Composition	100% Polyester	ASTM D 751-06		
Backing Weight	3.0 oz / yd ² ±10%	ASTM D 751-06		
Repeat	None			
Railroaded	No			
Put-up	30 yards			
Cleaning Code	W			
<u>Performance</u>	<u>Values</u>	<u>Test Method</u>		
Grab Tensile	114 lbs./in. x 100 lbs./in. min.	ASTM D 751-06		
Trap Tear	36 lbs./in. x 36 lbs./in. min.	ASTM D 751-06		
Seam Strength	62 lbs./in. x 47 lbs./in. min.	ASTM D 751-06		
Adhesion	6 lbs./in. x 6 lbs./in. min.	ASTM D 751-06		
Stretch @ 15# (MD×CD)	6% x 14%	ASTM D 751-06		
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)		
Blocking	No. 1 - Pass	TM5872		
Cold Crack Resistance	-20°F - Pass	CFFA-6a		
Crock Resistance	Dry-4; Wet-4	AATCC 8-2007		
Mildew Resistance	Pass	ASTM G-21		
Anti-Bacterial	Pass	AATCC 147-2004		
Pink Stain	Pass	ASTM 1428		
Wyzenbeek Abrasion	500,000 cycles, #10 cotton duck	ASTM D 4157-92		
Colorfastness to Water: Sea	Shade Change-5 / Staining -5	AATCC 106-2013		
Colorfastness to Light	650 hours	ASTM D 4329-05		
<u>Flammability</u>	<u>Values</u>	<u>Flammability</u>	<u>Values</u>	
California Bulletin 117-2013, Section 1	Pass	MVSS #302	Pass	
U.F.A.C. Class I	Pass	Boston Fire Dept. IX-1	Pass	
NFPA 260	Pass	FAA FAR 25.853	Pass	
I.M.O. A.652 (16) Sec. 8.2 & 8.3	Pass	NFPA 701 Small Scale	Pass	

Suitable Applications: Commercial; Outdoor/Marine

03/08/2017 - Revision: 5