



White Gold



Mercury



Zinc



Copper




Alloy



Aluminum



Barium



Rose Gold



Magnesium



Tungsten



Iridium



Colbalt



Onyx



Gunmetal

**Construction**

Surface Composition	100% Polycarbonate
Finished Width	54" min.
Backing Composition	85% Rayon, 15% Polyester
Put-up	30 yards
Repeat	None
Cleaning Code	WS
Railroaded	No

**Test Method**

ASTM D 751-89
ASTM D 751-89

**Performance**

Adhesion	4 lbs./in. × 4 lbs./in. min.
Grab Tensile	80 lbs./in. × 60 lbs./in. min.
Trap Tear	15 lbs./in. × 15 lbs./in. min.
Seam Strength	40 lbs./in. × 40 lbs./in. min.
Stretch at 15# MD (warp) × CD (fill)	12% × 20%
Stretch and Set	Stretch: Length – 4.0% Width – 22.0% Set: Length – 0.7% Width – 3.4%
Flex Resistance	25,000 cycles
Blocking	No. 1 - PASS
Seam Slippage	25 lbs. × 25 lbs.
Crock Resistance	Wet-5; Dry-5
Wyzenbeek Abrasion (#10 Cotton Duck)	500,000 cycles, #10 Cotton Duck
Hydrolysis Resistance	15 weeks
Colorfastness to Light	15 weeks
Cold Crack (5# roller)	650 hours
	-20°F

**Test Method**

ASTM D 751-89
ASTM D 751-89
ASTM D 751-89
ASTM D 751-89
ASTM D 5034-09
SAE J855
ASTM D 2097-91
FTMS 191A-TM5872
ASTM D 4034
AATCC 8-2001
ASTM D 4157-07
ASTM D 3690-02
ISO 5423: 1992 (E)
AATCC 16-2004
CFFA-6A

**Flammability**

California Technical Bulletin 117-2013, Sec. 1	Pass
FMVSS/CMVSS #302	Pass
IMO A.652(16)8.2	Pass
NFPA 260	Pass
U.F.A.C. Class I	Pass

**Environmental**

1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. REACH, RoHS, and LEED compliant

**Suitable Applications** Contract, Healthcare, Hospitality, Residential

**Cleaning and Disinfecting**

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare

The Mitchell Group  
7040 N. Austin Avenue | Niles, IL 60714  
847.647.7300 | mitchellfauxleathers.com