



Product Specifications

Mitchell Collection - BABY CROCK



<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>
Top Finish	PU	
Surface Composition	PVC	
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	33 oz./yd.	ASTM D 751-06
Thickness	1.2 mm \pm 10%	ASTM D 751-06
Total Weight	22 oz./yd ² \pm 10%	ASTM D 751-06
Backing Composition	70% Polyester / 30% Cotton	ASTM D 751-06
Backing Weight	3.5 oz. / yd ²	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	
<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	85 lbs./in. x 90 lbs./in. min.	ASTM D 751-06
Trap Tear	15 lbs./in. x 15 lbs./in. min.	ASTM D 751-06
Seam Strength	65 lbs./in. x 65 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. x 4 lbs./in. min.	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Wyzenbeek Abrasion	50,000 cycles, #10 cotton duck	ASTM D 4157-92
UV Stability	150 hours	ASTM D 4329-05
Crock Resistance	Dry-4; Wet-4	AATCC 8-2007
Stretch (MD x CD)	2% x 9% at 15 lbs.	ASTM D 751-06
<u>Flammability</u>		<u>Environmental</u>
California Bulletin 117-2013, Section 1	Pass	7p Free - Does not contains the following phthalates: DBP, BBP, DEHP, DOP, DNOP, DINP, DIDP Does not contain any flame retardant chemicals.
U.F.A.C. Class I	Pass	
NFPA 260	Pass	

Suitable Applications: Residential

Country of Origin: China

08/25/2016 - Revision: 3