



Product Specifications

Mitchell Collection - HAMPSTEAD



Technical Specs

<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% PVC	
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	26.8 oz/yd	ASTM D 751-06
Thickness	1.0 mm ±10%	ASTM D 751-06
Total Weight	17.8 oz./yd ² ±10%	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Backing Weight	4 oz / yd ²	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	40 yards	
Cleaning Code	W	

Performance

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	65 lbs./in. × 85 lbs./in. min.	ASTM D 751-06
Trap Tear	12 lbs./in. × 14 lbs./in. min.	ASTM D 751-06
Seam Strength	65 lbs./in. × 70 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	5%× 5%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	20 cycles - Pass	AATCC 8-2007
Wyzenbeek Abrasion	35,000 cycles, #10 cotton duck	ASTM D 4157-10
UV Stability	40 hours	ASTM D 4329-05

Flammability

MVSS302	Pass
California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass

Suitable Applications: Residential

Country of Origin: China

12/31/2015 - Revision: 4