



MITCHELL

Product Specifications

Mitchell Collection - JUBILEE



<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>
Surface Composition	PVC	
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	38 oz/yd	ASTM D 751-06
Thickness	1.6 mm ±10%	ASTM D 751-06
Total Weight	25.4 oz./yd ² ±10%	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Backing Weight	4 oz / yd ²	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	30-40 yards	
Cleaning Code	W	

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	80 lbs./in. × 83 lbs./in. min.	ASTM D 751-06
Trap Tear	16 lbs./in. × 18 lbs./in. min.	ASTM D 751-06
Seam Strength	65 lbs./in. × 70 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	5%× 5%	ASTM D 751-06
Flex Resistance	20,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	Wet-4; Dry-4	AATCC 8-2007
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-10
UV Stability	150 hours	ASTM D 4329

<u>Flammability</u>	
MVSS302	Pass
California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass

Suitable Application: Commercial

Country of Origin: China

09/15/2016 - Revision 4