



Product Specifications

Mitchell Collection - LAVISH



Technical Specs

| <u>Technical Specs</u> | <u>Values</u> | <u>Test Method</u> |
|------------------------|---------------------------------------|--------------------|
| Surface Composition | 100% Polyurethane | |
| Finished Width | 54" min. | ASTM D 751-06 |
| Weight at 54 inches | 25.5 oz./yd. | ASTM D 751-06 |
| Thickness | 1.2 mm \pm 10% | ASTM D 751-06 |
| Total Weight | 17.1 oz./yd ² \pm 10% | ASTM D 751-06 |
| Backing Composition | 50% Nylon/50% Polyurethane | ASTM D 751-06 |
| Backing Weight | 13.25 oz. / yd ² \pm 10% | ASTM D 751-06 |
| Repeat | None | |
| Railroaded | No | |
| Put-up | 30 yards | |
| Cleaning Code | W | |

Performance

| <u>Performance</u> | <u>Values</u> | <u>Test Method</u> |
|--------------------------------|---|--------------------|
| Grab Tensile | 120 lbs./in. \times 120 lbs./in. min. | ASTM D 751-06 |
| Trap Tear | 40 lbs./in. \times 40 lbs./in. min. | ASTM D 751-06 |
| Seam Strength | 120 lbs./in. \times 120 lbs./in. min. | ASTM D 751-06 |
| Adhesion | 5 lbs./in. \times 5 lbs./in. min. | ASTM D 751-06 |
| Stretch @ 15# (MD \times CD) | 4% \times 12% | ASTM D 751-06 |
| Puncture Resistance | 110 lbf | ASTM D 751-06 |
| Flex Resistance | 25,000 Cycles | ASTM D 2097-91 |
| Blocking | No. 1 - Pass | FTMS 191A-TM5872 |
| Crock Resistance | Dry-4; Wet-4 | AATCC 8-2007 |
| Hydrolysis Resistance | 7 weeks | ASTM D 3690-02 |
| | 10 weeks | ISO 5423: 1992 E |
| Wyzenbeek Abrasion | 100,000 cycles, #10 cotton duck | ASTM D 4157-13 |
| UV Stability | 200 hours (4-5) | AATCC 16 |
| Cold Crack (Roller Method) | -20°F | CFFA-6a |

Flammability

| | |
|---|------|
| California Bulletin 117-2013, Section 1 | Pass |
| UFAC Class I | Pass |
| NFPA 260 | Pass |
| IMO A.652(16) 8.2 & 8.3 | Pass |
| MVSS #302 | Pass |

Environmental

1. No polyvinyl chloride, plasticizers, phthalates, stabilizers, heavy metals or bisphenol A
2. No persistent organic pollutants. No toxic by-products
3. No chemical flame retardants
4. 99% of solvents captured and recycled.
5. RoHS, REACH and LEED compliant

Suitable Applications: Hospitality, Contract, Residential, RV

Country of Origin: China

02/12/2018 - Revision: 7