






Ash




Bark



Black




Chestnut




Chocolate



Cognac




Earth




Green Tea



Linen



Navy



Oxford



White

| Construction | Values | Test Method |
|---------------------|-------------------|---------------|
| Surface Composition | 100% Polyurethane | |
| Backing Composition | 100% Polyester | ASTM D 751-06 |
| Finished Width | 54" min. | ASTM D 751-06 |
| Repeat | None | |
| Railroaded | No | |
| Put-up | 30 yards | |
| Cleaning Code | W | |

| Performance | Values | Test Method |
|-----------------------|---------------------------------|------------------|
| Grab Tensile | 80 lbs./in. × 80 lbs./in. min. | ASTM D 751-06 |
| Trap Tear | 18 lbs./in. × 18 lbs./in. min. | ASTM D 751-06 |
| Seam Strength | 40 lbs./in. × 40 lbs./in. min. | ASTM D 751-06 |
| Adhesion | 4 lbs./in. × 4 lbs./in. min. | ASTM D 751-06 |
| Stretch @ 15# (MD×CD) | 10% × 20% | ASTM D 751-06 |
| Flex Resistance | 25,000 Cycles | ASTM D 2097-91 |
| Blocking | No. 1 - Pass | FTMS 191A-TM5872 |
| Crock Resistance | D-4; W-4 | AATCC 8-2007 |
| Wyzenbeek Abrasion | 100,000 cycles, #10 cotton duck | ASTM D 4157-92 |
| Hydrolysis Resistance | 7 weeks | ASTM D 3690-02 |
| UV Stability | 150 hours | ASTM D 4329-05 |

| Flammability | | Environmental |
|--|------|--|
| California Technical Bulletin 117-2013, Sec. 1 | Pass | 1. No anti-microbial additives |
| IMO A.652(16)8.2 | Pass | 2. Does not contain PFAS, PFOA |
| NFPA 260 | Pass | 3. Prop 65 compliant |
| U.F.A.C. Class I | Pass | 4. No chemical flame retardants, CA AB2998 compliant |
| | | 5. REACH, RoHS, and LEED compliant |

Suitable Applications Commercial, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare

The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com