



Aqua



Black




Buckskin



Burlap




Camel




Cherry



Cinnamon




Cream



Denim



Fog



Ivy



Lotion




Mist




Pebble



Pecan




Pine




Port



Rain



Smoke



Sunshine




Taupe



Walnut



Wheat



White

## Construction

Construction	Values	Test Method
Surface Composition	PVC	ASTM D 751-06
Finished Width	54" min.	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W/S	

## Performance

Performance	Values	Test Method
Grab Tensile	85 lbs./in. × 75 lbs./in. min.	ASTM D 751-06
Trap Tear	20 lbs./in. × 27 lbs./in. min.	ASTM D 751-06
Seam Strength	35 lbs./in. × 30 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	7.5% × 18%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Cold Crack Resistance	-20°F - Pass	CFFA-6a
Crock Resistance	Dry - 4; Wet - 4	AATCC 8-2016
Wyzenbeek Abrasion	1,300,000 cycles, #10 cotton duck	ASTM D 4157
Colorfastness to Light	650 hours, Grade 4-5	ASTM D 4329

## Flammability

California Technical Bulletin 117-2013, Sec. 1	Pass
FMVSS/CMVSS #302	Pass
IMO A.652(16)8.2	Pass
NFPA 260	Pass
U.F.A.C. Class I	Pass

## Environmental

1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. RoHS compliant – Phthalate free

## Suitable Applications

Contract, Healthcare, Hospitality, Residential

## Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.

