



Opal



Birch




Nugget



Apple



Breeze



Wave



Dark Orange



Maple



Hemp



Terra



Pewter



Armor

Construction	Values	Test Method
Surface Composition	100% PVC	
Backing Composition	100% Polyester	ASTM D 751-89
Finished Width	54" min.	ASTM D 751-89
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	
Performance	Values	Test Method
Grab Tensile	80 lbs./in. × 70 lbs./in. min.	ASTM D 5034-09
Trap Tear	15 lbs./in. × 15 lbs./in. min.	ASTM D 5587-07
Seam Strength	30 lbs./in. × 30 lbs./in. min.	ASTM D 1683-07A
Adhesion	3 lbs./in. × 3 lbs./in. min.	ASTM D 751-89
Flex Resistance	30,000 cycles	ASTM D 2097-03
Blocking	No. 1 - Pass	Fed. Std. 191 A , 5872
Crock Resistance	Dry-5; Wet-5	AATCC 8-2013
Wyzenbeek Abrasion	100,000 cycles, #10 Cotton Duck	ASTM D 4157-07
UV Stability	500 hours	ASTM G 154
Anti-bacterial	No growth	AATCC 147-2004
Mildew Resistance	No growth	ASTM G-21
Cold Crack (Roller Method)	-40°F - Pass	CFFA-6a

Flammability	Environmental
California Technical Bulletin 117-2013, Sec. 1	Pass 1. Does not contain PFAS, PFOA
IMO A.652(16)8.2	Pass 2. Prop 65 compliant
NFPA 260	Pass 3. No chemical flame retardants, CA AB2998 compliant
U.F.A.C. Class I	Pass 4. RoHS compliant – Phthalate free

## Suitable Applications Commercial

## Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.

