


White




Beige



Stone



Wheat



Honey



Buckskin



Pecan




Cafe



Chocolate



Burgundy



Gray




Dove



Black



Marine



Hunter

## Technical Specifications

Technical Specifications	Values	Test Method
Top Finish	Polyurethane	ASTM D 751-06
Surface Composition	PVC Foam	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Finished Width	54" min.	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	

## Performance

Performance	Values	Test Method
Grab Tensile	80 lbs./in. × 60 lbs./in. min.	ASTM D 751-06
Trap Tear	18 lbs./in. × 18 lbs./in. min.	ASTM D 751-06
Seam Strength	35 lbs./in. × 35 lbs./in. min.	ASTM D 751-06
Adhesion	3 lbs./in. × 3 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MD×CD)	2% × 6%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	Dry-4; Wet-4	AATCC 8-2007
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-13
UV Stability	150 hours	ASTM D 4329-05
Hydrolysis Resistance	5 weeks	ISO 1419: 1995

## Flammability

California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass
FMVSS/CMVSS #302	Pass

## Environmental

Does not contain any flame retardant chemicals.

## Suitable Applications

Hospitality

## Cleaning

Remove ordinary dirt and smudges with mild soap and water. Do not use chemical cleaners or disinfectants.