




Apple



Armor



Birch



Breeze



Dark Orange




Hemp



Maple



Nugget




Opal



Pewter



Terra



Wave

| Construction | Values | Test Method |
|---------------------|----------------|---------------|
| Surface Composition | 100% PVC | |
| Backing Composition | 100% Polyester | ASTM D 751-89 |
| Finished Width | 54" min. | ASTM D 751-89 |
| Repeat | None | |
| Railroaded | No | |
| Put-up | 30 yards | |
| Cleaning Code | W | |

| Performance | Values | Test Method |
|----------------------------|---------------------------------|------------------------|
| Grab Tensile | 80 lbs./in. × 70 lbs./in. min. | ASTM D 5034-09 |
| Trap Tear | 6 lbs./in. × 6 lbs./in. min. | ASTM D 5587-07 |
| Seam Strength | 30 lbs./in. × 30 lbs./in. min. | ASTM D 1683-07A |
| Adhesion | 3 lbs./in. × 3 lbs./in. min. | ASTM D 751-89 |
| Flex Resistance | 30,000 cycles | ASTM D 2097-03 |
| Blocking | No. 1 - Pass | Fed. Std. 191 A , 5872 |
| Crock Resistance | Dry-5; Wet-5 | AATCC 8-2013 |
| Wyzenbeek Abrasion | 100,000 cycles, #10 Cotton Duck | ASTM D 4157-07 |
| UV Stability | 500 hours | ASTM G 154 |
| Cold Crack (Roller Method) | -10°F - Pass | CFFA-6a |

| Flammability | | Environmental |
|--|------|--|
| California Technical Bulletin 117-2013, Sec. 1 | Pass | 1. No anti-microbial additives |
| IMO A.652(16)8.2 | Pass | 2. Does not contain PFAS, PFOA |
| NFPA 260 | Pass | 3. Prop 65 compliant |
| U.F.A.C. Class I | Pass | 4. No chemical flame retardants, CA AB2998 compliant |
| | | 5. RoHS compliant – Phthalate free |

Suitable Applications Commercial

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.