



Boots



Camel



Grey



Merlot



Pumice



Saddle

| Construction        | Values         | Test Method   |
|---------------------|----------------|---------------|
| Surface Composition | 100% PVC       | ASTM D 751-06 |
| Backing Composition | 100% Polyester | ASTM D 751-06 |
| Finished Width      | 54" min.       | ASTM D 751-06 |
| Repeat              | None           |               |
| Railroaded          | No             |               |
| Put-up              | 30 yards       |               |
| Cleaning Code       | W              |               |

| Performance          | Values                           | Test Method          |
|----------------------|----------------------------------|----------------------|
| Grab Tensile         | 175 lbs./in. × 137 lbs./in. min. | ASTM D 751-06        |
| Trap Tear            | 18 lbs./in. × 12 lbs./in. min.   | ASTM D 751-06        |
| Seam Strength        | 82 lbs./in. × 64 lbs./in. min.   | ASTM D 751-06        |
| Adhesion             | 8 lbs./in. × 7 lbs./in. min.     | ASTM D 751-06        |
| Stretch @15# (MD×CD) | 2% × 3%                          | ASTM D 751-06        |
| Flex Resistance      | 25,000 cycles                    | ASTM D 2097-03(2010) |
| Blocking             | No. 1 – Pass                     | FTMS 191A-TM5872     |
| Crock Resistance     | Dry-4-5; Wet-4-5                 | AATCC TM8-2016e      |
| Cold Crack           | 5# Roller Method, -40°F          | CFFA-6A              |
| Wyzenbeek Abrasion   | 100,000 cycles, #10 cotton duck  | ASTM D 4157-2013     |
| UV Stability         | 200 hours                        | ASTM D 4329-21       |

| Flammability                                   |      | Environmental                 |
|------------------------------------------------|------|-------------------------------|
| California Technical Bulletin 117-2013, Sec. 1 | Pass | 1. Phthalate free             |
| NFPA 260                                       | Pass | 2. REACH Compliant            |
| U.F.A.C. Class I                               | Pass | 3. No FR chemicals            |
|                                                |      | 4. No antimicrobial chemicals |
|                                                |      | 5. VOC-CA 01350-Pass          |

## Suitable Applications Residential

## Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel.

