




Aqua




Bella




Bourbon




Charcoal



Claret



Cream



Dark Sky



Deep Sea




Dusky Blue




Falcon



Flame



Fog



Indigo



Kalahari




Khaki



Marigold



Navy



Nickel



Ocean




Orange



Pewter



Rustic




Sage




Sea Mist




Smoke



Stone



Storm



Taupe



Teal



Wheat

| Construction | Values | Test Method |
|---------------------|--|---------------|
| Content | 45% Polyurethane, 55% Recycled Polyester | |
| Backing Composition | 100% Global Recycled Standard Polyester | ASTM D 751-06 |
| Finished Width | 54" min. | |
| Put-up | 30 yards | ASTM D 751-06 |
| Repeat | None | |
| Cleaning Code | W/S | |

| Performance | Values | Test Method |
|--------------------------------------|---------------------------------|------------------|
| Adhesion | 4 lbs./in. × 4 lbs./in. min. | ASTM D 751-06 |
| Grab Tensile | 80 lbs./in. × 120 lbs./in. min. | ASTM D 751-06 |
| Trap Tear | 45 lbs./in. × 50 lbs./in. min. | ASTM D 751-06 |
| Seam Strength | 45 lbs./in. × 110 lbs./in. min. | ASTM D 751-06 |
| Stretch at 27# MD (warp) × CD (fill) | 6% × 24% | SAE J855, 2002 |
| Flex Resistance | 25,000 cycles | ASTM D 2097-91 |
| Blocking | No. 1 - PASS | FTMS 191A-TM5872 |
| Crock Resistance | Dry: 4.5 / Wet: 4.5 | AATCC 8-2007 |
| Wyzenbeek Abrasion | 250,000 cycles, #10 Cotton Duck | ASTM D 4157-13 |
| Hydrolysis Resistance | 15 weeks | ISO 1419 |
| UV Stability | 200 hours | ASTM D 4329-05 |
| Cold Crack (5# roller) | -40°F | CFFA-6A |

Environmental

| | |
|--|--|
| No PVC, plasticizers, phthalates, formaldehyde, stabilizers, or heavy metals | No halogenated FR Chemicals - CAL AB2998 compliant |
| No persistent organic pollutants (POPs) | Conflict mineral free |
| No DMF or DMFA | Prop 65 compliant |
| Zero chemical solvents | LBC Red List compliant |
| No ozone-depleting chemicals | CAL 01350 VOC compliant/low VOCs |
| No anti-microbial additives | LEED - prequalified |
| Biocide, BPA, and TRIS Free | RoHS, REACH compliant |

Flammability

| | | | |
|------------------|------|------------------|------|
| CA TB117-2013 | Pass | NFPA 260 | Pass |
| FMVSS/CMVSS #302 | Pass | U.F.A.C. Class I | Pass |
| IMO A.652(16)8.2 | Pass | | |

Suitable Applications Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare



The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com