




Blue Jay



Cotinga



Dove



Ibis



Mandarin



Oriole



Parrotlet



Robin



Starling



Turaco



Vireo



Warbler



Wren

Construction	Values	Test Method	
Chemical Coating Face	7% Silicone Protection and 93% Bio-Attributed PU build on Susterra PDO		
Top Finish Protection	Hydro-Sil™ Finish		
Backing Composition	100% Polyester	ASTM D 751-06	
Finished Width	54" min.		
Put-up	30 yards	ASTM D 751-06	
Repeat	None		
Cleaning Code	W/S		
Performance	Values	Test Method	
Adhesion	4 lbs./in. x 4 lbs./in. min.	ASTM D 751-06	
Grab Tensile	80 lbs./in. x 80 lbs./in. min.	ASTM D 751-06	
Trap Tear	15 lbs./in. x 15 lbs./in. min.	ASTM D 751-06	
Seam Strength	40 lbs./in. x 40 lbs./in. min.	ASTM D 751-06	
Stretch at 27# MD (warp) x CD (fill)	2% x 8%	SAE J855, 2002	
Flex Resistance	25,000 cycles	ASTM D 2097-91	
Blocking	No. 1 - PASS	FTMS 191A-TM5872	
Crock Resistance	Dry Grade: 4.0 / Wet Grade: 4.0	AATCC 8-2007	
Wyzenbeek Abrasion	100,000 cycles, #10 Cotton Duck	ASTM D 4157-13	
Hydrolysis Resistance	24 weeks	ISO 5423: 1992 E	
UV Stability	200 hours	ASTM D 4329-05	
Cold Crack (5# roller)	-40°F	CFFA-6A	
Environmental			
No PVC, plasticizers, phthalates, formaldehyde, stabilizers, or heavy metals	No halogenated FR Chemicals - CAL AB2998 compliant		
No persistent organic pollutants (POPs)	Conflict mineral free		
No DMF or DMFA	Prop 65 compliant		
Zero chemical solvents	LBC Red List compliant		
No ozone-depleting chemicals	CAL 01350 VOC compliant/low VOCs		
No anti-microbial additives	LEED - prequalified		
Biocide, BPA, and TRIS Free	RoHS, REACH compliant		
Flammability			
CA TB117-2013	Pass	NFPA 260	Pass
FMVSS/CMVSS #302	Pass	U.F.A.C. Class I	Pass
IMO A.652(16)8.2	Pass		
Suitable Applications	Contract, Healthcare, Hospitality, Residential		

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare



The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com