Nubuck




Bourbon


Charcoal


Clove


Mount Hood


Navy


Nickel


Molasses


Oak


Pomegranate


Silk

sta*kleen POLYCARBONATE

Product Specifications

Nubuck

Construction	Values	Test Method
Surface Composition	100% Polycarbonate	
Finished Width	54" min.	
Backing Composition	50% Rayon / 50% Polyester	ASTM D 751-89
Put-up	30 yards	ASTM D 751-89
Repeat	None	
Cleaning Code	WS	
Railroaded	No	

Performance	Values	Test Method
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-89
Grab Tensile	120 lbs./in. × 100 lbs./in. min.	ASTM D 751-89
Trap Tear	15 lbs./in. × 15 lbs./in. min.	ASTM D 751-89
Seam Strength	40 lbs./in. × 40 lbs./in. min.	ASTM D 751-89
Stretch at 15# MD (warp) ×CD (fill)	12% × 20%	ASTM D 5034-09
Stretch and Set	Stretch: Length – 4.0% Width – 22.0% Set: Length – 0.7% Width – 3.4%	SAE J855
Flex Resistance	25,000 cycles	ASTM D 2097-91
Blocking	No. 1 – Pass	FTMS 191A-TM5872
Seam Slippage	25 lbs. × 25 lbs.	ASTM D 4034
Crock Resistance	Dry – 5; Wet – 5	AATCC 8-2001
Wyzenbeek Abrasion (#10 Cotton Duck)	500,000 cycles	ASTM D 4157-07
Hydrolysis Resistance	30 weeks	ISO 1419: 1995, Method C
Colorfastness to Light	650 hours	AATCC 16-2004
Cold Crack (5# roller)	-20°F	CFFA-6A

Flammability	
California Technical Bulletin 117-2013, Sec. 1	Pass
FMVSS/CMVSS #302	Pass
IMO A.652(16)8.2	Pass
NFPA 260	Pass
U.F.A.C. Class I	Pass

Environmental

1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. REACH, RoHS, and LEED compliant

Suitable Applications

Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.

MITCHELL Performance Faux Leathers | CLOROX HEALTHCARE

The Mitchell Group is a compatibility partner with Clorox Healthcare

The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com