





Moth



Fog




Aqua



Meadow



Rust




Seafoam



Stream



Steel



Spa



Mint



Fox



Aegean



Rain



Gray



Moss



Ocean



Popsicle




Cobalt



Smoke



Dusk



Sunshine



Grotto



Eggplant



Marlin



Charcoal



Pigeon

Construction	Values	Test Method
Surface Composition	100% Polycarbonate	
Backing Composition	50% Polyester, 50% Rayon	ASTM D 751-89
Finished Width	54" min.	ASTM D 751-89
Put-up	30 yards	
Repeat	None	
Cleaning Code	W/S	
Stain Resistant	Yes	

Performance	Values	Test Method
Adhesion	4 lbs. × 4 lbs.	ASTM D 751-89
Breaking Strength	80 lbs. × 60 lbs.	ASTM D 751-89
Trap Tear	15 lbs. × 15 lbs.	ASTM D 751-89
Seam Strength	40 lbs. × 40 lbs.	ASTM D 751-89
Stretch at 15# MD (warp) ×CD (fill)	8% × 12%	ASTM D 5034-09
Flex Resistance	25,000 cycles	ASTM D 2097-91
Blocking	No. 1 - PASS	FTMS 191A, 5872
Seam Slippage	25 lbs. × 25 lbs.	ASTM D 4034
Crock Resistance	D-5; W-5	AATCC 8-2001
Wyzenbeek Abrasion	300,000 cycles, #10 Cotton Duck	ASTM D 4157-07
Mildew Resistance	Pass - No growth	ASTM G-21
Anti-Bacterial	Pass - No growth	AATCC 147-2004
	10 weeks	ASTM D 3690-02
Hydrolysis Resistance	15 weeks	ISO 5423: 1992 (E)
Colorfastness to Light	1000 hours	AATCC 16-2004
Cold Crack (5# roller)	-20°F	CFFA-6A

Flammability	Pass
California Technical Bulletin 117-2013, Sec. 1	Pass
CMVSS #302	Pass
IMO A.652(16)8.2	Pass
NFPA 260	Pass
U.F.A.C. Class I	Pass

Environmental
1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. REACH, RoHS, and LEED compliant

Suitable Applications Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare

The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com