



Product Specifications

Mitchell Collection - EEL



Technical

<u>Technical</u>	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% PVC	
Finished Width	54" min.	ASTM D 751-06
Backing Composition	70% Polyester / 30% Cotton	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	30 yards	
Cleaning Code	WS	
Protective Finish	Ez-Kleen™	

Performance

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	85 lbs./in. x 90 lbs./in. min.	ASTM D 751-06
Trap Tear	15 lbs./in. x 15lbs./in. min.	ASTM D 751-06
Seam Strength	65 lbs./in. x 65 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. x 4 lbs./in. min.	ASTM D 751-06
Stretch @ 15# (MDxCD)	2% x 9%	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Crock Resistance	Dry-4; Wet-4	AATCC 8-2007
Blue Dye Transfer	Dry-4-5; Wet-4	Chrysler Method: LP-463KC-04-03
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-92
UV Stability	150 hours	ASTM D 4329-05

Flammability

<u>Flammability</u>	<u>Values</u>	<u>Environmental</u>
California Bulletin 117-2013, Section 1	Pass	Does not contain any flame retardant chemicals.
U.F.A.C. Class I	Pass	Does not contain anti-microbial additives
NFPA 260	Pass	Phthalate free
IMO 2010, Part 8, Section 3.1	Pass	REACH compliant.

Suitable Applications: Contract, Healthcare, Hospitality, Residential