



Product Specifications

Mitchell Collection - LAREDO



Technical

Surface Composition
Backing Composition
Finished Width
Repeat
Railroaded
Put-up
Cleaning Code

Values

PVC
70% Polyester / 30% Cotton
54" min.
V: 8.5" / H: 8.5 "
No
30 yards
W

Test Method

ASTM D 751-06
ASTM D 751-06

Performance

Grab Tensile
Trap Tear
Seam Strength
Adhesion
Stretch @ 15# (MD×CD)
Flex Resistance
Blocking
Crock Resistance
Wyzenbeek Abrasion
UV Stability

Values

85 lbs./in. × 90 lbs./in. min.
15 lbs./in. × 15 lbs./in. min.
65 lbs./in. × 65 lbs./in. min.
4 lbs./in. × 4 lbs./in. min.
2% × 9%
25,000 Cycles
No. 1 - Pass
D-4; W-4
90,000 cycles, #8 cotton duck
40 hours (no color change)

Test Method

ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 2097-03(2010)
FTMS 191A-TM5872
AATCC 8-2007
ASTM D 4157-92
ASTM D 4329-05

Flammability

California Bulletin 117, Section E.
U.F.A.C. Class I
NFPA 260

Pass
Pass
Pass

Environmental

7p Free - Does not contains the following phthalates: DBP, BBP, DEHP, DOP, DNOP, DINP, DIDP

Suitable Applications: Residential