



Product Specifications

Mitchell Collection - CRAZY HORSE



Technical Specs

<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% Polyurethane	
Backing Composition	95% Polyester, 5% Cotton	ASTM D 751-89
Finished Width	54" min.	ASTM D 751-89
Put-up	30 yards	
Repeat	None	
Cleaning Code	W	
Railroaded	No	

Performance

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	100 lbs./in. × 100 lbs./in. min.	ASTM D 5034-09
Trap Tear	15 lbs./in. × 15 lbs./in. min.	ASTM D 5587-07
Seam Strength	35 lbs./in. × 35 lbs./in. min.	ASTM D 1683-07A
Adhesion	3 lbs./in. × 3 lbs./in. min.	ASTM D 751-89
Flex Resistance	25,000 cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	Fed. Std. 191 A , 5872
Wyzenbeek Abrasion	25,000 cycles, #10 Cotton Duck	ASTM D 4157-07
Hydrolysis Resistance	3 weeks	ISO 5423: 1992 E
UV Stability	40 hours (Grade 4)	AATCC 16-2004
Crock Resistance	20 cycles - Pass	Fed. Std. 191 A , 5651
Stretch at 15# MD (warp) ×CD (fill)	2 % × 2 %	ASTM D 751-89

Flammability

California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass
FMVSS & CMVSS 302	Pass

Suitable Applications: Residential; RV