



Product Specifications

Mitchell Collection - VALENCIA



Technical Specs

	<u>Values</u>	<u>Test Method</u>
Surface Composition	PVC	ASTM D 751-06
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	33 oz./yd. ±10%	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	30 yards	
Cleaning Code	W	
Protective Finish	Ez-Kleen™	

Performance

	<u>Values</u>	<u>Test Method</u>
Grab Tensile	110 lbs./in. × 110 lbs./in. min.	ASTM D 751-06
Trap Tear	35 lbs./in. × 35 lbs./in. min.	ASTM D 751-06
Seam Strength	35 lbs./in. × 35 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-13
UV Stability	250 hours, Grade 4-5	ASTM D 4329-05
Crock Resistance	Dry - 4-5; Wet - 4-5	AATCC 8-2016
Stretch (MD×CD)	7% × 30%	ASTM D 751-06

Flammability

California Bulletin 117-2013, Section 1	Pass
NFPA 260	Pass
UFAC Class I	Pass
FMVSS/CMVSS #302	Pass
IMO 2010, Part 8, Section 3.1	Pass

Environmental

Does not contain any flame retardant chemicals.
Phthalate free
RoHS compliant.

Suitable Applications: Hospitality, Contract, Residential

Country of Origin: China

07/31/2019 - Revision: 5