





MITCHELLTM
COLLECTION

LAVISH






Daisy




Swan




Maple



Khaki




Driftwood



Sky



Cool Gray




Pearl



Saddle




Sumac




Slate




Cove



Midnight



Dusk



Anthracite

Technical Specifications

Technical Specifications	Values
Surface Composition	100% Polyurethane
Backing Composition	50% Nylon / 50% Polyurethane
Finished Width	54" Width
Repeat	None
Railroaded	No
Put-up	30 yards
Cleaning Code	W

Test Method

ASTM D 751-06
ASTM D 751-06

Performance

Grab Tensile	120 lbs./in. × 120 lbs./in. min.
Trap Tear	40 lbs./in. × 40 lbs./in. min.
Seam Strength	120 lbs./in. × 120 lbs./in. min.
Adhesion	5 lbs./in. × 5 lbs./in. min.
Stretch @ 15# (MD×CD)	4% × 12%
Puncture Resistance	110 lbf
Flex Resistance	25,000 cycles
Blocking	No. 1 - Pass
Crock Resistance	Wet-4; Dry-4
Hydrolysis Resistance	7 weeks
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck
UV Stability	200 hours (4-5)
Cold Crack (#5 roller)	-20°F

Test Method

ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 751-06
ASTM D 2097-91
FTMS 191A-TM5872
AATCC 8-2007
ASTM D 3690-02
ISO 5423: 1992 E
ASTM D 4157-13
AATCC 16
CFFA-6a

Flammability

California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass
IMO A.652(16) 8.2 & 8.3	Pass
MVSS #302	Pass

Environmental

1. No polyvinyl chloride, plasticizers, phthalates, stabilizers, heavy metals or bisphenol A
2. No persistent organic pollutants. No toxic by-products
3. No chemical flame retardants
4. 99% of solvents captured and recycled
5. RoHS, REACH and LEED compliant

Suitable Applications

Hospitality, Contract, Residential, RV

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting.

Dry with a soft, lint-free cloth or towel.