



MITCHELLTM
COLLECTION

LUXURY



Beige



Jesse James



Wild Bunch



Pecan



Dalton Gang



Coffee



Black



Graphite

Technical Specifications	Values	Test Method
Surface Composition	100% Polyurethane	
Backing Composition	100% Polyester	ASTM D 751-89
Finished Width	54" min.	ASTM D 751-89
Repeat	None	
Railroaded	No	
Put-up	40 yards	
Cleaning Code	W	

Performance		Test Method
Grab Tensile	150 lbs./in. × 100 lbs./in. min.	ASTM D 5034-09
Trap Tear	20 lbs./in. × 20 lbs./in. min.	ASTM D 5587-07
Seam Strength	70 lbs./in. × 60 lbs./in. min	ASTM D 1683-11A
Adhesion	4 lbs./in. × 4 lbs./in. min.	ASTM D 751-89
Stretch @ 15# (MD×CD)	2% × 9%	ASTM D 751-89
Flex Resistance	25,000 Cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	Fed. Std. 191 A , 5872
Crock Resistance	Wet-4; Dry-4	AATCC 8-2007
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-13
Hydrolysis Resistance	3 weeks	ISO 1419-1995 E
UV Stability	40 hours	AATCC 16-2004

Flammability	
California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass

Suitable Applications	Residential
-----------------------	-------------

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel.