



## Product Specifications

# Ez-Kleen - SEDONA



### Technical Specs

	<u>Values</u>	<u>Test Method</u>
Surface Composition	PVC	ASTM D 751-06
Finished Width	54" min.	ASTM D 751-06
Backing Composition	100% Polyester	ASTM D 751-06
Repeat	None	ASTM D 751-06
Railroaded	No	
Put-up	30 yards	
Cleaning Code	WS	
Protective Finish	Ez-Kleen™	

### Performance

	<u>Values</u>	<u>Test Method</u>
Grab Tensile	110 lbs./in. x 110 lbs./in. min.	ASTM D 751-06
Trap Tear	35 lbs./in. x 35 lbs./in. min.	ASTM D 751-06
Seam Strength	35 lbs./in. x 35 lbs./in. min.	ASTM D 751-06
Adhesion	4 lbs./in. x 4 lbs./in. min.	ASTM D 751-06
Flex Resistance	25,000 Cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	FTMS 191A-TM5872
Wyzenbeek Abrasion	100,000 cycles, #10 cotton duck	ASTM D 4157-13
UV Stability	250 hours, Grade 4-5	ASTM D 4329-05
Crock Resistance	Dry - 4-5; Wet - 4-5	AATCC 8-2016
Blue Jean Dye Transfer Test	Dry - 4-5; Wet - 4	Chrysler Method: LP-463KC-04-03
Stretch (MDxCD)	7% x 30%	ASTM D 751-06

### Flammability

California Bulletin 117-2013, Section 1	Pass
NFPA 260	Pass
UFAC Class I	Pass
FMVSS/CMVSS #302	Pass
IMO 2010, Part 8, Section 3.1	Pass

### Environmental

Does not contain any flame retardant chemicals.

Does not contain anti-microbial additives

Phthalate free

RoHS compliant.

**Suitable Applications:** Contract, Healthcare, Hospitality, Residential