



White Gold



Mercury



Zinc



Copper




Alloy



Aluminum



Barium



Rose Gold



Magnesium



Tungsten



Iridium



Colbalt



Onyx



Gunmetal

Construction

Surface Composition
Finished Width
Backing Composition
Put-up
Repeat
Cleaning Code
Railroaded

Values

100% Polycarbonate
54" min.
85% Rayon, 15% Polyester
30 yards
None
WS
No

Test Method

ASTM D 751-89
ASTM D 751-89

Performance

Adhesion
Grab Tensile
Trap Tear
Seam Strength
Stretch at 15# MD (warp) x CD (fill)

Stretch and Set

Flex Resistance
Blocking
Seam Slippage
Crock Resistance
Wyzenbeek Abrasion (#10 Cotton Duck)
Mildew Resistance
Anti-Bacterial
Hydrolysis Resistance

Colorfastness to Light
Cold Crack (5# roller)

Values

4 lbs./in. x 4 lbs./in. min.
80 lbs./in. x 60 lbs./in. min.
15 lbs./in. x 15 lbs./in. min.
40 lbs./in. x 40 lbs./in. min.
12% x 20%

Stretch: Length – 4.0% Width – 22.0%
Set: Length – 0.7% Width – 3.4%

25,000 cycles
No. 1 - PASS
25 lbs. x 25 lbs.
Wet-5; Dry-5
500,000 cycles, #10 Cotton Duck
Pass - No growth
Pass - No growth
15 weeks
15 weeks
650 hours
-20°F

Test Method

ASTM D 751-89
ASTM D 751-89
ASTM D 751-89
ASTM D 751-89
ASTM D 5034-09

SAE J855

ASTM D 2097-91
FTMS 191A-TM5872
ASTM D 4034
AATCC 8-2001
ASTM D 4157-07
ASTM G-21
AATCC 147-2004
ASTM D 3690-02
ISO 5423: 1992 (E)
AATCC 16-2004
CFFA-6A

Flammability

California Technical Bulletin 117-2013, Sec. 1 Pass
FMVSS/CMVSS #302 Pass
IMO A.652(16)8.2 Pass
NFPA 260 Pass
U.F.A.C. Class I Pass

Environmental

1. No anti-microbial additives
2. Does not contain PFAS, PFOA
3. Prop 65 compliant
4. No chemical flame retardants, CA AB2998 compliant
5. REACH, RoHS, and LEED compliant

Suitable Applications Contract, Healthcare, Hospitality, Residential

Cleaning and Disinfecting

Remove ordinary dirt and smudges with mild soap and water. A 10:1 ratio of water to bleach solution may be used as a disinfectant. Rinse the surface with clean water after disinfecting. Dry with a soft, lint-free cloth or towel. We recommend that you use Clorox Healthcare and Clorox Pro products to disinfect Mitchell products in commercial settings.



The Mitchell Group is a compatibility partner with Clorox Healthcare

The Mitchell Group
7040 N. Austin Avenue | Niles, IL 60714
847.647.7300 | mitchellfauxleathers.com