



**Product Specifications**

**Sta-Kleen - SOLEIL**



<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% PU	
Backing Composition	100% Polyester	ASTM D 751-89
Finished Width	54" min.	ASTM D 751-89
Put-up	30 yards	
Repeat	None	
Railroaded	No	
Cleaning	W/S	

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	95 lbs./in. x 80 lbs./in. min.	ASTM D 5035-09
Trap Tear	15 lbs./in. x 15 lbs./in. min.	ASTM D 5587-07
Seam Strength	40 lbs./in. x 35 lbs./in. min.	ASTM D 1683-07A
Adhesion	4 lbs./in. x 4 lbs./in. min.	ASTM D 751-89
Stretch @15# (MD×CD)	2% x 12%	ASTM D 751-89
Flex Resistance	25,000 Cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	Federal Standard 191A, 5304
Crock Resistance	Dry-4; Wet-4	Federal Standard 191A, 5651
Wyzenbeek Abrasion	300,000 cycles, #10 Cotton Duck	ASTM D 4157-07
Hydrolysis Resistance	7 weeks	ASTM D3690-02
UV Stability	1000 hours	AATCC 16-2004
Blue Dye Transfer Resistance	Dry 4-5; Wet 4-5	LP-463KC-04-03
Anti-Bacterial	Pass	ASTM E 1428-99
Mildew Resistance	Pass	ASTM G-21
Cold Crack	-20°F	CFFA-6A

**Flammability**

California Bulletin 117-2013, Section 1	Pass
U.F.A.C. Class I	Pass
NFPA 260	Pass
IMO A.652(16)8.2	Pass

**Environmental**

Does not contain PFAS,  
PFOA or formaldehyde.  
RoHS and REACH compliant.



**Suitable Applications:** Hospitality, Contract, Healthcare, Residential