



MITCHELL

Product Specifications

Grand Slam - ROULETTE



<u>Technical Specs</u>	<u>Values</u>	<u>Test Method</u>	
Surface Composition	100% PVC		
Finished Width	54" min.	ASTM D 751-06	
Weight at 54 inches	36.3 oz/yd	ASTM D 751-06	
Thickness	1.25 mm ±10%	ASTM D 751-06	
Total Weight	24.2 oz./yd ² ±10%	ASTM D 751-06	
Backing Composition	100% Polyester	ASTM D 751-06	
Backing Weight	3.0 oz / yd ² ±10%	ASTM D 751-06	
Repeat	None		
Railroaded	No		
Put-up	30 yards		
Cleaning Code	W		
<u>Performance</u>	<u>Values</u>	<u>Test Method</u>	
Grab Tensile	119 lbs./in. × 91 lbs./in. min.	ASTM D 751-06	
Trap Tear	32 lbs./in. × 49 lbs./in. min.	ASTM D 751-06	
Seam Strength	53 lbs./in. × 44 lbs./in. min.	ASTM D 751-06	
Adhesion	5 lbs./in. × 4 lbs./in. min.	ASTM D 751-06	
Stretch @ 15# (MD×CD)	8% × 21%	ASTM D 751-06	
Flex Resistance	25,000 Cycles	ASTM D 2097-03(2010)	
Blocking	No. 1 - Pass	FTMS 191A-TM5872	
Cold Crack Resistance	-20°F - Pass	CFFA-6a	
Crock Resistance	Dry-4; Wet-4	AATCC 8-2007	
Mildew Resistance	Pass	ASTM G-21	
Anti-Bacterial	Pass	AATCC 147-2004	
Pink Stain	Pass	ASTM 1428	
Wyzenbeek Abrasion	500,000 cycles, #10 cotton duck	ASTM D 4157-92	
Colorfastness to Water: Sea	Shade Change-5 / Staining -5	AATCC 106-2013	
Colorfastness to Light	650 hours	ASTM D 4329-05	
<u>Flammability</u>	<u>Values</u>	<u>Flammability</u>	<u>Values</u>
California Bulletin 117-2013, Section 1	Pass	MVSS #302	Pass
U.F.A.C. Class I	Pass	Boston Fire Dept. IX-1	Pass
NFPA 260	Pass	FAA FAR 25.853	Pass
I.M.O. A.652 (16) Sec. 8.2 & 8.3	Pass	NFPA 701 Small Scale	Pass



Suitable Applications: Commercial; Outdoor/Marine

05/24/2018 - Revision: 6