



Product Specifications

Mitchell Collection - SPLENDID



Technical Specs

<u>Technical Specs</u>	<u>Values</u>	<u>Test Method Used</u>
Surface Composition	60% Acrylic / 40% Nylon	
Finished Width	54" min.	ASTM D 751-06
Weight at 54 inches	22.0 oz./yd. ±10%	ASTM D 751-06
Thickness	2.0 mm ±10%	ASTM D 751-06
Total Weight	14.8 oz./yd ² ±10%	ASTM D 751-06
Backing Composition	80% Polyester / 20% Cotton	ASTM D 751-06
Backing Weight	3.0 oz. / yd ² ±10%	ASTM D 751-06
Repeat	None	
Railroaded	No	
Put-up	40 yards	
Cleaning Code	W	

Performance

<u>Performance</u>	<u>Values</u>	<u>Test Method</u>
Grab Tensile	100 lbs. x 100 lbs. min.	ASTM D5034
Seam Slippage	25 lbs. x 25 lbs. min.	ASTM D4034
Tearing Strength	10 lbs. x 10 lbs. min.	ASTM D2261
Crock Resistance	Dry-5; Wet-5	AATCC 8
Wyzenbeek Abrasion	200,000 cycles	ASTM D 4157
Colorfastness to Light	40 hours - Grade 4-5	AATCC 16.3-2012

Flammability

California Bulletin 117-2013, Section 1	Pass
NFPA 260	Pass
UFAC Class I	Pass
FMVSS 302 / CMVSS 302	Pass
I.M.O. A.652(16) 8.2 & 8.3	Pass

Suitable Applications: Commercial

Country of Origin: China

8/04/2016 - Revision: 4