



## Product Specifications

# Mitchell Collection: SUNBURST



### Technical Specs

	<u>Values</u>	<u>Test Method</u>
Surface Composition	100% PVC	
Finished Width	54" min.	ASTM D 751-89
Weight at 54 inches	33.0 oz./yd. ± 10%	ASTM D 751-89
Thickness	1.2 mm ±10%	ASTM D 751-89
Total Weight	22.0 oz./yd <sup>2</sup> ±10%	ASTM D 751-89
Backing Composition	70% polyester, 30% cotton	ASTM D 751-89
Backing Weight	3.5 oz. / yd <sup>2</sup> ±10%	ASTM D 751-89
Put-up	30 yards	
Repeat	None	
Railroaded	No	
Cleaning Code	W	

### Performance

	<u>Values</u>	<u>Test Method</u>
Grab Tensile	85 lbs./in. × 90 lbs./in. minimum	ASTM D 5034-09
Trap Tear	15 lbs./in. × 15 lbs./in. minimum	ASTM D 5587-07
Seam Strength	65 lbs./in. × 65 lbs./in. minimum	ASTM D 1683-07A
Adhesion	4 lbs./in. × 4 lbs./in. minimum	ASTM D 751-89
Stretch at 15# MD (warp) ×CD (fill)	2% × 9%	ASTM D 751-89
Flex Resistance	25,000 cycles	ASTM D 2097-91
Blocking	No. 1 - Pass	Fed. Std. 191 A , 5872
Wyzenbeek Abrasion	36,000 cycles, #10 Cotton Duck	ASTM D 4157-07
UV Stability	150 hours	ASTM D 4329-05
Crock Resistance	Wet - Class 4; Dry - Class 4	AATCC 8-2007
Cold Crack (Roller Method)	Pass -20°F	CFFA-6a

### Flammability

California Bulletin 117-2013, Section 1	PASS
U.F.A.C Class I	PASS
NFPA 260	PASS

### Environmental

No chemical flame retardants

Suitable Applications: Residential

Country of Origin: China

08/25/2016 - Revision: 2