



Product Specifications

Sta-Kleen® - TUCSON



| <u>Technical Specs</u> | <u>Values</u> | <u>Test Method</u> |
|------------------------|--------------------------------|--------------------|
| Surface Composition | 100% Polyurethane | |
| Finished Width | 54" min. | ASTM D 751-06 |
| Weight at 54 inches | 22.4 oz./yd. ±10% | ASTM D 751-06 |
| Thickness | 1.0 mm ±10% | ASTM D 751-06 |
| Total Weight | 16.2 oz./yd ² ±10% | ASTM D 751-06 |
| Backing Composition | 85% Polyester/15% Cotton | ASTM D 751-06 |
| Backing Weight | 4.9 oz. / yd ² ±10% | ASTM D 751-06 |
| Repeat | None | |
| Railroaded | No | |
| Put-up | 30 yards | |
| Cleaning Code | W/S | |

| <u>Performance</u> | <u>Values</u> | <u>Test Method</u> |
|-------------------------------------|---------------------------------|------------------------|
| Grab Tensile | 80 lbs./in. x 80 lbs./in. min. | ASTM D 751-06 |
| Trap Tear | 15 lbs./in. x 15 lbs./in. min. | ASTM D 751-06 |
| Seam Strength | 40 lbs./in. x 40 lbs./in. min. | ASTM D 751-06 |
| Adhesion | 4 lbs./in. x 4 lbs./in. min. | ASTM D 751-06 |
| Stretch at 15# MD (warp) xCD (fill) | 2% x 7% | ASTM D 751-06 |
| Flex Resistance | 25,000 cycles | ASTM D 2097-91 |
| Blocking | No. 1 - Pass | Fed. Std. 191 A , 5872 |
| Crock Resistance | Dry-4; Wet-4 | AATCC 8-2007 |
| Wyzenbeek Abrasion | 300,000 cycles, #10 Cotton Duck | ASTM D 4157-07 |
| Hydrolysis Resistance | 10 weeks | ASTM D 3690-02 |
| | 10 weeks | ISO 1419: 1995 |
| Colorfastness to Light | 200 hours | ASTM D 4329-05 |
| Blue Dye Transfer Resistance | Dry-4-5; Wet-4-5 | LP-463KC-04-03 |
| Anti-Bacterial | Pass | AATCC 147-2004 |
| Mildew Resistance | Pass | ASTM G-21 |
| Cold Crack (#5 roller) | -20°F | CFFA-6A |

| <u>Flammability</u> | <u>Values</u> |
|---|---------------|
| California Bulletin 117-2013, Section 1 | Pass |
| NFPA 260 | Pass |
| UFAC Class I | Pass |
| IMO A.652(16)8.2 | Pass |



| <u>Environmental</u> |
|--|
| Does not contain PFAS, PFOA or formaldehyde. |
| Does not contain chemical flame retardants. |
| RoHS and REACH compliant. |

Suitable Applications: Hospitality, Contract, Healthcare, Residential

Country of Origin: China

08/15/2018 - Revision: 5